

## **COMMUNITY DEVELOPMENT DEPARTMENT Building & Safety Inspection Division**

221 West Pine St./PO Box 3006, Lodi, CA 95241-1910 (209) 333-6714

## Authorization to Connect Utility Service Building Inspection Division Site Review

AC		<u>Policy</u>	and Procedure No.: B-[	)8]-[26A] January 20 <sup>-</sup>	<u>11-Rev. 11/07/11</u>	
ADDRESS:		Suite/Unit:				
Proposed O	ccupancy: Group	p Division	Occupant load		SF	
-		/ NO Commercial Kitchen	-			
Sec incli requ	tion 3408). The suding structural, puring structural, puring structural, por	I change the occupancy from a structure may be required to bolumbing, mechanical, electrical rtions of the buildings proposed a Building Code, Chapter 11B.	be brought into com al, energy and acce d for change of occ	npliance with all c ess requirements supancy shall cont	current code provisior (California accessibil	ns lity
GENERAL	CODE-RELATED	ITEMS REQUIRING CORREC	TION:			
□ Exterior:	□ Foundation	□ Siding □ Service	□ Label main el	ectric meter pane	I for address served	
	□ Wiring □	□ Protect/Remove exposed elec	trical cables 🗀 La	es		
		ss visible from road: 4 in min up in min over 55 ft away)	to 25 ft away, 6 in r	nin 26 - 40 ft awa	y, 9 in min 41-55 ft	
□ Interior:	□ Provide exit	t signs 🗆 Office area(s) - se	e notes □ Shop	/Storage area(s) -	see notes	
	□ Provide "this	Provide "this door to remain unlocked during business hours" sign(s) above entry door(s)				
	□ Provide fire	extinguishers: 1 for each 3000	ft <sup>2</sup> max and 75 ft tra	vel distance - Typ	e 2A:10-B:C	
	□ Current serv	vice tag for Type I kitchen hood	system   Curre	ent service tag for	fire extinguishers	
□ Mechanical Equipment:		□ Duct into non-conditioned	space □ Vent	□ Vent termination/Combustion air		
		□ Condensate system	□ See r	notes below		
□ Electrical Systems:		□ Remove extension cords	□ Cove	□ Cover open junction/Outlet boxes		
		□ Label breakers at electrica	l panel(s) □ See r	notes below		
□ Plumbing Systems:		<ul> <li>□ Provide 2 seismic straps at water heater 1 @ upper 1/3 of tank &amp; 1 @ lower 1/3 of tant</li> <li>□ Provide ¾" pressure/temperature relief drain sloped to exterior pointing down min. 6" max 24" above ground level (No PVC/No flex pipe)</li> <li>□ Remove substandard plumbing</li> </ul>			ık &	
□ Fire Sprinklers:		□ 5 yr. Certification □ See notes below				
□ See notes below		□ See attached cor	rection notice			
Notes:						
•	,	) <b>YES / NO</b> □ Building □ Plumbi	•			l
		YES / NO Type of plans require				
		g Department for permit and				
		n done, please call the inspec r the following work day.	tion request line (2	<u>209) 333-6716. Pl</u>	ease call before	

Inspected by: \_\_\_\_\_\_ Date: \_\_\_\_\_ Phone: \_\_\_\_\_